




Data sheet

Customer : Jan Philipp Wuesten Elektronik
 Drawing No. : 9311
 23.11.01

page 1 / 1

Type : A16055016039



Ø D : 16 mm
 L : 39 mm
 l : 40 mm
 d : 0,8 mm

Terminals : Wire

Electrical Parameters

| | | |
|--|--------------------|----------------|
| Rated Capacitance (C _R) 100 Hz / 20 °C | 16 µF | |
| Tolerance | -10 / +30 % | |
| Rated Voltage (U _R) | 550 V | |
| Surge Voltage (U _S) max. 5 x 1 min / h | 600 V | |
| Reverse Voltage (U _U) max. 1 s | 2 V | |
| Leakage Current (I _L) U _R / 5 min / 20 °C | 52 µA | |
| ESR typ. 100 Hz / 20°C | 5970 mΩ | |
| Tan δ typ. 100 Hz / 20°C | 6 % | |
| Z max. 10 kHz / 20°C | 5400 mΩ | |
| ESL typ. | 20 nH | |
| Rated Ripple Current (I _R) 100 Hz / 85 °C | 0,2 A | |
| Useful Life @ I _R , U _R , 85°C | 5000 h | |
| IEC Climatic category / Standards | 40/ 85/56 | IEC 384 |
| Applications | tube amplifier | |
| Your article No. / Project | | |